



Standard Features:

- Sealed Electrical System
- Easy Engine Access
- Commercial Grade Engine
- Battery Disconnect Switch
- Tight Turning Radius
- Front Hydraulic Couplers - Drip free
- Heavy Duty Welded Steel Frame
- Full Front & Rear Skid Plates

Optional Accessories Include:

- Adjustable Weight Transfer System
- Power Take Off
- Rear Lighting

The Ventrac SSV makes it easy and efficient to manage snow and ice on sidewalks. The SSV is a dedicated Sidewalk Snow Vehicle with an industry-first 36" working width in order to allow access to the tightest areas of any property. The SSV allows for more reduction of hand labor and walk-behind equipment than ever before. It's also designed with a full arsenal of commercial quality snow removal attachments and de-icing options that are engineered to provide a system that can handle any winter storm. The wait for a proper sidewalk snow machine is finally over.



SPECIFICATIONS

SSV	
Model	Kawasaki Gasoline
Stock Codes	39.61100
Accessory Options:	PTO, Weight Transfer & Rear Work Lights
Engines	
Engine Manufacturer	Kawasaki
Engine	FS600V
Max Operating Speed	3600rpm
Horsepower	18.5
Peak Torque	32.5 @ 2200rpm
Displacement	603cc
Cylinders	2
Engine Oil	Ventrac Full Synthetic 10W30
Fuel Type	Gasoline
Fuel Capacity	3.3 gal (12.5L)
Fuel Economy	1.0 gal/hr
Slope Rating	10° (18% Grade)
Alternator	20 Amps
Dimensions	
Weight	970 lb (440 kg)
Weight with accessories kits	1020 lb (463 kg)
Wheelbase	28 inch (71 cm)
Length	67 inch (171 cm)
Width	34 inch (86 cm)
Height	55 inch (140 cm)
Turning Radius	0 inch (0 cm)
Electrical	
Battery	500 CCA (Group 51R)
Voltage	12 Volts
Battery Disconnect	150A Circuit Breaker
Fuses	Mini Fuse
Hitch and PTO (optional)	
Front Hitch	Ventrac Mount System
Electrical PTO clutch with Brake	Warner GT-2000
Lighting	
Head Lights	(2) 1200 Lumens LED Lights
Rear Work Lights	(2) 1200 Lumens LED Lights
Drivetrain	
Type	Hydrostatic
Pump	Hydro-Gear tandem, variable displacement piston type
Wheel Motors	Parker TJ Geroller
Hydraulic Oil Filter (Suction)	25 Micron, replaceable
Hydraulic Oil Filter (Pressurized)	10 Micron, replaceable



Instrumentation

Gauges	Hour Meter, Fuel Level
Indicator Lights	PTO, Parking Brake, Low Voltage, Low Oil Pressure

Controls

Forward/Reverse	Hydraulic Lever Control
Attachment Lift	Joystick
Auxiliary Hydraulics	Joystick
Throttle	Dash Mounted
Front Hitch Lock	Hitch Mounted
PTO Belt Tensioner	Machine Spring
Weight Transfer	3 Position
Steering	Hydraulic Lever Steer

Tires

Standard (All Terrain)	18x8.5-10 (46 x 22 x 25.4 cm)
------------------------	-------------------------------

Travel Speed (F/R)

High Range	8 mph (12.8 kph) forward 5 mph (8 kph) reverse
------------	---

All specifications subject to change without notice or obligation



500 Venture Drive
Orrville, OH 44667
1.866.836.8722

Fax: 330.683.0000
www.ventrac.com
info@ventrac.com