

TORO®

ULTRA BUGGY® e2500-THL

MATERIAL HANDLING

Raise productivity on the jobsite with Toro's electric high-lift Ultra Buggy e2500-THL. With a 76" dump height, operators can effortlessly clear a 30-yard dumpster with up to 1,250-lbs of material. Powered by Toro's patented HyperCell® Battery technology, the Ultra Buggy e2500-THL delivers up to eight hours of quiet performance to easily transition from outdoor jobsites to noise-sensitive indoor spaces. Save time, boost efficiency and save crews from excess fatigue.

KEY FEATURES

76" Dump Height – Confidently clear a 6-ft height on a 30-yard dumpster.

Carrying Capacity – The steel tub boasts 12.8 cu ft carrying capacity and can unload 2,500-lbs at standard dump height and up to 1,250-lbs at full high-lift dump height.

Powered by HyperCell – Toro's proprietary battery technology offers reduced noise, zero engine exhaust emissions and all-day runtime.

Intuitive Controls – Move materials in minutes with controls designed for smooth handling.

Narrow Design – At 31.5", the Ultra Buggy e2500-THL easily maneuvers in tight spaces and can fit through standard doorways and gates.





ULTRA BUGGY® e2500-THL

MATERIAL HANDLING

KEY SPECIFICATIONS

Electric High-Lift Ultra Buggy (model 68142)	
Battery Capacity Chemistry	13 kWh Lithium Ion
Dimensions (LxWxH)	101.5"x31.5"x59.3 (257.8 x 80.0 x 150.6 cm)
Platform down	88.7"x31.5"x59.3
Platform up	(225.2 x 80.0 x 150.6 cm)
Weight	2,650 lbs (1,202 kg)
Tub Volume	12.8 ft³ (0.3 m³)
Max Load Capacity	
Standard dump height	2,500 lbs (1,133.9 kg)
Full dump height	1,250 lbs (566.9 kg)
Speed	5 mph (8.04 km/h) forward 3 mph (4.82 km/h) reverse
Run Time	Up to 8 hours
Charging Type	100-240 Volt, on-board
Charging Time	80% in 4 hours at 240V 100% in 6 hours at 240V
Discharge Height	
Scissor down	41.7" (105.9 cm)
Scissor raised	76" (193.0 cm)
Distributed Floor Pressure	
Unloaded	1.15 PSI
Loaded	1.55 PSI



76" DUMP HEIGHT

DUMP INTO A 30-YARD DUMPSTER

